
















участок:		LITE		дистанция	страница
				3,800	1
ДИСТАНЦИЯ		НАПРАВЛЕНИЕ	ИНФОРМАЦИЯ	ДО КВ-СТОП	
ИНТЕРВАЛ (КМ)					
0,00		 START/СТАРТ			
0,00			т. WP0	3,800	
0,07		 E3 !			
0,07			т. WP1	3,730	
0,26					
0,19			т. WP2	3,540	
0,39					
0,13			т. WP3	3,410	
0,53		-v ! C 195° HP			
0,14			т. WP4	3,270	











➡ 0,08

участок:		LITE		дистанция	страница				
				3,800	2				
ДИСТАНЦИЯ		НАПРАВЛЕНИЕ	ИНФОРМАЦИЯ	ДО КВ-СТОП					
ИНТЕРВАЛ (КМ)									
0,61							P - V т. WP5 3,190		
0,08 6									
0,67							E3 ! C 100° MVS EMP т. WP6 3,130		
0,06 7									
1,10							(KS) 1 т. WP7 2,700		
0,43 8									
1,14							!!  C 340° et 160 m } } } !! т. WP8 2,660		
0,04 9									
1,32							!! E3  т. WP9 2,480		
0,18 10									

➡ 0,17

участок:		LITE		дистанция		страница	
				3,800		3	
ДИСТАНЦИЯ		НАПРАВЛЕНИЕ		ИНФОРМАЦИЯ		ДО КВ-СТОП	
ИНТЕРВАЛ (КМ)							
1,49						т. WP10 2,310	
0,17 11							
1,60						т. WP11 2,200	
0,11 12							
1,85						т. WP12 1,950	
0,25 13							
1,90				G !!		т. WP13 1,900	
0,05 14							
1,98						т. WP14 1,820	
0,08 15							

➡ 0,06

участок:		LITE		дистанция		страница	
				3,800		4	
ДИСТАНЦИЯ		НАПРАВЛЕНИЕ	ИНФОРМАЦИЯ	ДО КВ-СТОП			
ИНТЕРВАЛ (КМ)							
2,04							
0,06							
2,07				HP MVS EMP  ТРИАЛ			
0,03							
2,19				G   С 340°			
0,12							
2,36							
0,17							
2,49				 E3			
0,13							

➡ 0,06

участок:		LITE		дистанция		страница	
				3,800		5	
ДИСТАНЦИЯ		НАПРАВЛЕНИЕ		ИНФОРМАЦИЯ		ДО КВ-СТОП	
ИНТЕРВАЛ (КМ)							
2,55				G !!! HP C 30°		т. WP20 1,250	
0,06 <div>21</div>							
2,78				(KS) 2 D HP C 225° et 30 m et 60 m MVS EMP		т. WP21 1,020	
0,23 <div>22</div>							
3,08						т. WP23 0,720	
0,30 <div>23</div>							
3,17				HP C 135°		т. WP24 0,630	
0,09 <div>24</div>							
3,22				HP P// NBX CX. C 150°		т. WP25 0,680	
0,05 <div>25</div>							

➡ 0,13

участок:		LITE	дистанция 3,800	страница 6
ДИСТАНЦИЯ ИНТЕРВАЛ (КМ)		НАПРАВЛЕНИЕ	ИНФОРМАЦИЯ	ДО КВ-СТОП
3,35			G MVS EMP C 180° т. WP26	!!!! 0,450
0,13	26			
3,47			(KS) 3	т. WP27
0,12	27			
3,74			-V ↗ держаться левее	т. WP29
0,27	28			
3,80				т. WPO
0,06	29			